DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 36 N., R. 50 E., MDM, NEVADA

	1. 30 N., K. 30 E., MDM, NETADA
CHAINS	N. 87° 26' E., bet. secs. 27 and 34.
	Over mountainous land, covered with sagebrush, buckbrush, chokecherry and native grass.
23.60	Trail road on ridge, bears N. and S.
41.27	Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
;	T36N R50E
	\(\frac{\scrt{5.27}}{\scrt{5.34}}\)
	1986
	Set a steel fence post, 5½ ft. long, alongside the aluminum post.
58.00	Spur, projects SE.
77.20	Creek, 20 1ks. wide, 2 ft. deep, course SE.
78.21	Intersect the W. bdy. of sec. 31, T. 36 N., R. 51 E.
	Point for the closing cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T36N R50E R51E CCS 27 S 31
	1986
	Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the
	aluminum post.
·	From this corner, the standard cor. of T. 36 N., R. 51 E., hereinbefore described, bears SOUTH, 15.20 chs. dist.
	Point for the E k sec. cor. of sec. 34, at midpoint bet. the closing cors. and on the W. bdy. of sec. 6, T. 35 N., R. 51 E.
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T36N
	R50E
	1986
	1300