

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
T. 11 N., R. 39 E., MDM, NEVADA

CHAINS	
	<p>Deposit the original cornerstone alongside the aluminum post and raise a mound of stone, 2½ ft. base, 2½ ft. high, S. of cor.</p>
	<p>N. 89° 51' W., beginning new measurement.</p>
	<p>Over rolling land.</p>
21.20	<p>Wash, 35 lks. wide, 2 ft. deep, drains WNW.</p>
38.17	<p>The closing cor. of secs. 31 and 32, T. 12 N., R. 39 E., hereinafter described.</p>
40.65	<p>The cor. of secs. 5, 6, 31 and 32, Tps. 11 and 12 N., Rs. 39 E., monumented with a mound of stone. No marked stone found. This mound of stone is accepted as the best available evidence of the position of the original corner. This corner will now refer to secs. 5 and 6 only.</p>
	<p>At the corner point</p>
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p>
	<p style="text-align: center;">T12N R39E S 31 S 6 S 5 T11N R39E</p>
	<p style="text-align: center;">1986</p>
	<p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p>
	<p>N. 89° 58' W., along the N. bdy. of sec. 6.</p>
	<p>Over rolling land, through scattered sagebrush, shadscale, rabbit brush and native grass.</p>
7.70	<p>Wash, 20 lks. wide, 3 ft. deep, drains SW.</p>
10.40	<p>Wash, 65 lks. wide, 6 ft. deep, drains SW.</p>
30.80	<p>Wash, 35 lks. wide, 3 ft. deep, drains WNW.</p>
37.52	<p>The S ¼ sec. cor. of sec. 31, T. 12 N., R. 39 E., hereinafter described.</p>
40.30	<p>Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. This corner will now refer to sec. 6 only.</p>
	<p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.</p>
	<p style="text-align: center;">T12N R39E ¼ S 6 T11N R39E</p>
	<p style="text-align: center;">1986</p>