

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 12 N., R. 39 E., MDM, NEVADA

CHAINS	
	S. 0° 03' E., bet. secs. 32 and 33. Over rolling land.
2.40	Improved gravel road, bears E. and W.
8.60	Wash, 20 lks. wide, 2 ft. deep, drains W.
14.20	Improved gravel road, bears E. and W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33. Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.  T12N R39E $\frac{1}{4}$ S 32 S 33  1986
66.60	Wash, 60 lks. wide, 3 ft. deep, drains SW.
67.60	Fence, bears NW. and SE.
68.60	Wash, 20 lks. wide, 4 ft. deep, drains SW.
80.00	Point for the 80 $\frac{1}{16}$ sec. cor. of secs. 32 and 33. Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.  80 $\frac{1}{16}$ S 32 S 33  1986  Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.
85.20	Wash, 15 lks. wide, 2 ft. deep, drains WSW.
88.50	Intersect the N. bdy. of sec. 4, T. 11 N., R. 39 E. Point for the closing cor. of secs. 32 and 33. Set an aluminum post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with aluminum cap mkd.  T12N R39E C C S 32 S 33 <u>S 4</u> T11N R39E  1986  Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  From this corner, the cor. of secs. 4 and 5, T. 11 N., R. 39 E., hereinbefore described, bears N. 89° 44' W., 1.38 chs. dist.