

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 12 N., R. 39 E., MDM, NEVADA

CHAINS	
78.00	Improved gravel road, bears ESE. and WNW.
82.36	The cor. of secs. 30 and 31, on the W. bdy. of the Tp.  Land, rolling. Soil, sandy clay loam. Undergrowth, sagebrush and native grass.
	From the cor. of secs. 29, 30, 31 and 32.  S. 0° 03' E., bet. secs. 31 and 32.  Over rolling land.
15.10	Improved gravel road, bears E. and W.
35.60	Improved gravel road, bears NNW. and SSE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.  Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.  T12N R39E $\frac{1}{4}$ S 31   S 32  1986
80.00	Point for the 80 1/16 sec. cor. of secs. 31 and 32.  Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.  80 1/16 S 31   S 32  1986  Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
86.00	Wash, 25 lks. wide, 3 ft. deep, drains W.
88.33	Intersect the N. bdy. of sec. 5, T. 11 N., R. 39 E.  Point for the closing cor. of secs. 31 and 32.  Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.  T12N R39E C C S 31   S 32 <u>S 5</u> T11N R39E  1986  Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.