

DEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES,  
TOWNSHIP 21 NORTH, RANGE 20 EAST, MDM, NEVADA

| CHAINS |  |
|--------|--|
|        | Set a steel fence post, 5½ ft. long, alongside the aluminum post.  |
| 38.00  | Ravine, drains W.  |
| 40.00  | The cor. of secs. 3, 4, 9 and 10, monumented with a basalt stone, 20X12X10 ins., firmly set and exposed 10 ins. above ground, plainly mkd. with 5 grooves on S. face and 3 grooves on E. face. |
|        | At the corner point  |
|        | Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.   |
|        | <div style="text-align: center;"> T21N R20E<br/> S 4 S 3<br/> S 9 S 10 </div>  |
|        | 1987   |
|        | Deposit the original cornerstone alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.  |
|        | N. 0° 03' W., bet. secs. 3 and 4.  |
|        | Over rolling mountainous land, through scattered sagebrush, cheatgrass and juniper.  |
| 14.00  | Rocky spur, slopes W.  |
| 19.95  | Point for the S 1/16 sec. cor. of secs. 3 and 4.   |
|        | Set an aluminum post, 30 ins. long, 2½ ins. diam., on solid rock over a cross (X), in a mound of stone, 4 ft. base to top, with aluminum cap mkd.  |
|        | <div style="text-align: center;"> S 1/16<br/> S 4 S 3 </div>   |
|        | 1987   |
|        | Set a steel fence post, 5½ ft. long, alongside the aluminum post.  |
| 35.50  | Spur, projects WSW.  |
| 39.90  | The ¼ sec. cor. of secs. 3 and 4, monumented with a lava stone, 18X12X12 ins., firmly set and exposed 8 ins. above ground, plainly mkd. ¼ on W. face.  |
|        | At the corner point  |
|        | Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd.                                      |