

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
TOWNSHIP 21 NORTH, RANGE 20 EAST, MDM, NEVADA

CHAINS	
40.10	Trail road, bears NE. and SW.
40.46	The cor. of secs. 4, 5, 8 and 9.
	N. 0° 12' E., bet. secs. 4 and 5.
	Over rolling land, through scattered sagebrush and cheatgrass.
0.20	Trail road, bears E. and W.
8.50	Wash, 10 lks. wide, 1 ft. deep, drains NE.
20.00	Point for the S 1/16 sec. cor. of secs. 4 and 5.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	<div style="text-align: center;">S 1/16 S 5 S 4</div>
	1987
	Set a steel fence post, 5½ ft. long, alongside the aluminum post.
40.00	The ¼ sec. cor. of secs. 4 and 5, monumented with a granite stone, 16X8X8 ins., firmly set and exposed 8 ins. above ground, plainly mkd. ¼ on W. face.
	At the corner point
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.
	<div style="text-align: center;">T21N R20E ¼ S 5 S 4</div>
	1987
	Deposit the original cornerstone alongside the aluminum post.
	N. 0° 02' E., beginning new measurement.
	Over rolling land.
2.80	Trail road, bears E. and W.
20.00	Point for the N 1/16 sec. cor. of secs. 4 and 5, at proportionate distance.
	Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	<div style="text-align: center;">N 1/16 S 5 S 4</div>
	1987