

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 39 N., R. 18 E., MDM, NEVADA

CHAINS	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 39 N., R. 18 E., MOUNT DIABLO MERIDIAN, NEVADA
	<p>Reestablishment of a Portion of the Survey Executed by C. F. Putman and W. F. Benson, U.S. Deputy Surveyors, in 1880, and the Retracement Executed by J. D. Archer, U.S. Transitman in 1911.</p>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.</p>
	<p>N. 0° 18' E., bet. secs. 35 and 36.</p>
	<p>Over mountainous land, through scattered sagebrush, rabbitbrush, bunchgrass and juniper.</p>
39.62	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T39N R18E $\frac{1}{4}$ S 35 S 36</p>
	<p style="text-align: center;">1986</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
70.00	<p>Ravine, drains ENE.</p>
79.24	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a trapstone, 20X12X10 ins., firmly set in a mound of stone and plainly mkd. with 1 groove on S. face and 1 groove on E. face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T39N R18E S 26 S 25 S 35 S 36</p>
	<p style="text-align: center;">1986</p>
	<p>Deposit the original cornerstone alongside the iron post.</p>
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of T. 39 N., R. 19 E., executed concurrently under this same Group.</p>