

316

DEPENDENT RESURVEY OF A PORTION OF
THE SOUTH BOUNDARY,
T. 44 N., R. 20 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF
THE SOUTH BOUNDARY,
T. 44 N., R. 20 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
G. W. Garside, U.S. Deputy Surveyor, in 1879
and
the Survey and Retracement Executed by
W. F. Benson and C. F. Putnam, U.S. Deputy Surveyors,
in 1880.

The cor. of secs. 4, 5, 32 and 33, monumented with a
trapstone, 14X12X4 ins., dimly mkd. with 4 grooves on
the E. face and 2 grooves on the W. face, firmly set in
an embedded mound of stone. This cor. now refers to
secs. 32 and 33 only.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins.
in the ground to solid rock and in a mound of stone, 3
ft. base to top, with brass cap mkd.

T44N R20E
S 32|S 33
S 4
T43N R20E

1985

Deposit the original cornerstone alongside the iron
post.

N. 89° 37' W., along the S. bdy. of sec. 32.

Over mountainous land, covered with scattered juniper,
sagebrush and native grass.

- 3.00 Rounded ridge, bears N. and S.
 - 4.10 Bluff, bears NE. and SW.
 - 10.20 The closing cor. of secs. 4 and 5, T. 43 N., R. 20 E.,
hereinafter described.
 - 16.20 Ravine, drains SW.
 - 27.10 Spur, projects S.
 - 33.30 Ravine, drains NW.
 - 37.60 Spur, projects NW.
 - 38.85 Point for the ¼ sec. cor. of secs. 5 and 32, at
proportionate distance; there is no remaining evidence
of the original corner. This cor. now refers to sec.
32 only.
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground to solid rock and in a mound of stone, 3
ft. base to top, with brass cap mkd.