43 357

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 43 N., R. 20 E., MDM, NEVADA

· · · ·	1. 43 N., K. 20 E., MDM, NETADA
CHAINS	From this corner, the E ¼ sec. cor. of sec. 6, hereinbefore described, bears S. 1°00' W., 1.55 chs. dist.
	From the cor. of secs. 4, 5, 8 and 9.
	N. 0°02' W., bet. secs. 4 and 5.
	Over rolling mountainous land, covered with scattered timber and undergrowth.
40.00	Point for the ½ sec. cor. of secs. 4 and 5.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T43N R20E
	s 5 s 4
	1985
74.00	Edge of rocky bluff, bears NE. and SW.
77.75	Intersect the S. bdy. of sec. 32, T. 44 N., R. 20 E.
	Point for the closing cor. of secs. 4 and 5.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T44N R20E
	<u>S 32</u> <u>S 51S 4</u>
	CIC T43N R20E
	1985
	Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this corner, the cor. of secs. 32 and 33, T. 44 N., R. 20 E., hereinbefore described, bears S. 89° 37' E., 10.20 chs. dist.
	Land, rolling mountainous. Soil, rocky clay loam. Timber, scattered juniper; undergrowth, scattered sagebrush and native grass.
	Point for the N $\frac{1}{4}$ sec. cor. of sec. 5, is on the S. bdy. of sec. 32, T. 44 N., R. 20 E., and at 40.00 chs. in departure from the closing cor. of secs. 4 and 5.