

## TOWNSHIP 44 NORTH, RANGE 19 EAST, MDM, NEVADA

<p>CHAINS</p>	<p>The geographic position for the true point for the <math>\frac{1}{4}</math> section corner of sections 8 and 9, is at latitude <math>41^{\circ} 44' 56.87''</math> N. and longitude <math>119^{\circ} 52' 02.22''</math> W., as calculated from U.S.C. &amp; G.S. Bench Mark "L-49," located in section 8.</p> <p>The geographic position for the southeast corner of the township, is at latitude <math>41^{\circ} 41' 04.8''</math> N. and longitude <math>119^{\circ} 47' 22.6''</math> W., as calculated along section lines.</p> <p>The mean magnetic declination was found to be <math>18\frac{1}{2}^{\circ}</math> E.</p> <hr/> <p style="text-align: center;">DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 44 N., R. 19 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by G. W. Garside, U.S. Deputy Surveyor in 1879 and the Retracement Executed by W. F. Benson and C. F. Putnam, U.S. Deputy Surveyors in 1880.</p> <hr/> <p>The point for the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., falls in an improved gravel road, at a point 30 ft. EAST of a corner of fences, from which fences bear W., N. and S. This position was pointed out by local resident Aurey Smith. This point is harmoniously related with other identified original corners in the area and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a steel spike, 4 ins. long, flush with surface of the road</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., set 24 ins. in the ground, with a collar of stone, for a reference monument, bears S. <math>37^{\circ} 21'</math> W., 67 lks. dist., with brass cap mkd. T43N R19E S5 RM 44 FT TO COR 1985 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., set 24 ins. in the ground, with a collar of stone, for a reference monument, bears N. <math>37^{\circ} 21'</math> E., 67 lks. dist., with brass cap mkd. T44N R19E S33 RM 44 FT TO COR 1985 and an arrow pointing to the corner.</p> <p>S. <math>89^{\circ} 36'</math> E., bet. secs. 4 and 33.</p> <p>Over nearly level land, covered with scattered sagebrush and native grass.</p> <p>0.43 Corner of fences, from which fences bear N. and E.</p> <p>20.20 Corner of fences, from which fences bear S., E. and W.</p>
---------------	--