

366

DEPENDENT RESURVEY OF A PORTION OF
THE SOUTH BOUNDARY,
T. 44 N., R. 19 E., MDM, NEVADA

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T44N R19E S 32 ¼ S 5 T43N</p> <p style="text-align: center;">1985</p> <p>Deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/>	
	<p>N. 89° 48' W., beginning new measurement.</p>	
	<p>Over rolling mountainous land.</p>	
9.30	<p>Trail road, bears N. and S.</p>	
9.50	<p>Fence, bears E. and S.</p>	
27.30	<p>Trail road, bears N. and S.</p>	
36.80	<p>Same trail road, bears NNE. and SSW.</p>	
39.94	<p>The cor. of secs. 5, 6, 31 and 32, monumented with a trapstone, 12X9X4 ins., firmly set in an embedded mound of stone, plainly mkd. with 6 grooves on the N. face and no other marks visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T44N R19E S 31 S 32 S 6 S 5 T43N</p> <p style="text-align: center;">1985</p> <p>Deposit the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/>	
39.96	<p>N. 89° 12' W., bet. secs. 6 and 31.</p> <p>Over mountainous land, covered with medium densities of juniper and scattered sagebrush and native grass.</p> <p>The ¼ sec. cor. of secs. 6 and 31, monumented with a trapstone, 36X10X6 ins., firmly set in a mound of stone, on the edge of a rocky bluff bearing NNE. and SSW., dimly mkd. ¼ on the N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p>	