

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 44 N., R. 19 E., MDM, NEVADA

CHAINS	39.69	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		<p style="text-align: center;">T44N R19E R20E <math>\frac{1}{4}</math> S 12 S 7</p>
		1985
		Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.
	79.38	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
		<p style="text-align: center;">T44N R19E R20E S 1 S 6 <u>S 12 S 7</u></p>
		1985
		Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
		From this corner, U.S.G.S. triangulation station "LONG," monumented with a standard brass tablet set in bedrock, with brass tablet mkd. "LONG 1966," bears S. $87^{\circ} 57'$ E., (mean bearing), 42.62 chs. dist.
		N. $0^{\circ} 48'$ E., bet. secs. 1 and 6.
		Over nearly level land, covered with scattered sagebrush, rabbitbrush and shadscale.
	15.80	Trail road, bears WNW. and ESE.
	19.40	Fence, bears E. and W.
	39.69	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		<p style="text-align: center;">T44N R19E R20E <math>\frac{1}{4}</math> S 1 S 6</p>
		1985