

441

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES  
OF SECS. 1 AND 2,  
T. 47 N., R. 39 E., MDM, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">S 31S 2 C C T47N R39E 1987</p> <p>Deposit the original cornerstone alongside the aluminum post.</p> <p>From this corner, Mile Post No. 180, on the Nevada-Oregon State Line, hereinbefore described, bears S. 89° 05' W., 2.41 chs. dist.</p>
	<p>SURVEY OF THE SUBDIVISION OF SECTION 1, T. 47 N., R. 39 E., MOUNT DIABLO MERIDIAN, NEVADA</p>
	<p>From the ¼ sec. cor. of secs. 1 and 12.</p> <p>N. 0° 23' W., on the N-S center line of sec. 1.</p> <p>Over mountainous land, through scattered sagebrush and cheatgrass.</p>
11.60	Draw, drains NW.
20.70	Draw, drains SW.
40.08	<p>Point for the center ¼ sec. cor. of sec. 1, at intersection with the E-W center line.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 6 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T47N R39E C¼ S 1 1987</p>
47.50	Top of ledge, bears ENE. and WSW.
80.40	<p>Point for the C-80 1/16 sec. cor. of sec. 1.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">C 1/16 S 1 C 80 1987</p>
81.40	East Fork Quinn River, 30 lks. wide, 1 ft. deep, course WSW.
82.40	Trail road, bears ENE. and WSW.