

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL SOUTH,
THROUGH A PORTION OF RANGE 59 EAST

CHAINS	DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL SOUTH, THROUGH A PORTION OF RANGE 59 EAST
	<p>Reestablishment of the Survey Executed by J. M. Brunt and W. H. Proctor, U.S. Deputy Surveyors, in 1881.</p> <hr/> <p>The standard cor. of secs. 34 and 35, monumented with a brass highway tablet, firmly set and in a 6 in. diam. well casing with lid, unable to read marks on tablet. This tablet is accepted as a careful and faithful perpetuation of the position of the original corner.</p> <p>from which:</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 41° 06' E., 100 lks. dist., with brass cap mkd. S 35 RM T20S R59E 1987 66 FT, and an arrow pointing to the cor.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 44° 53' W., 100 lks. dist., with brass cap mkd. S 34 RM T20S R59E 1987 66 FT, and an arrow pointing to the cor.</p> <p>The cor. is located beneath the center line of Charleston Boulevard, which bears E. and W.</p> <p>N. 89° 42' W., along the S. bdy. of sec. 34.</p> <p>Over gently rolling land, along Charleston Boulevard.</p>
8.01	The closing cor. of secs. 2 and 3, T. 21 S., R. 59 E., monumented with a railroad spike, 1 in. square, firmly set flush in ground, mkd. as described in the field notes of the dependent resurvey of T. 21 S., R. 59 E., executed concurrently under this same Group.
33.00	Leave Charleston Boulevard, enter rolling land.
41.06	Point for the standard ¼ sec. cor. of sec. 34, at proportionate distance; there is no remaining evidence of the original corner.
	POINT NOT MONUMENTED
49.11	The N ¼ sec. cor. of sec. 3, T. 21 S., R. 59 E., monumented with a stainless steel post, 2½ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 21 S., R. 59 E., executed concurrently under this same Group.
61.40	Ravine, drains SSE.
70.90	Ravine, drains SE.
82.12	The standard cor. of secs. 33 and 34, monumented with a limestone, 20X12X8 ins., firmly set showing 10 ins. above ground and plainly mkd. with 3 grooves on E. and W. faces and 6 grooves on N. face.