

480

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 21 S., R. 59 E., MDM, NEVADA

CHAINS

39.28

True point for the cor. of secs. 1, 6, 7 and 12.

From this point, the witness cor. of secs. 1, 6, 7 and 12, bears N. 85° 41' W., 1.01 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone. The retracement of the W. bdy. of sec. 7 revealed that this witness corner was placed W. of true point instead of E. of true point as the official record indicates.

The 1957 field note record indicates the brass cap was mkd. WC on W. side of cap, however the brass cap is mkd. as follows:

$$\begin{array}{c} \text{T21S} \\ \text{R58E R59E} \\ \text{S } 1 | \text{S } 6 \rightarrow \text{WC} \\ \text{S } 12 | \text{S } 7 \end{array}$$

1957

Add the marks 1987 to the brass cap.

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES
T. 21 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by J. M. Brunt
and W. H. Proctor, U.S. Deputy Surveyors,
in 1881

The cor. of secs. 1, 2, 35 and 36, on the S. bdy. of
the Tp.

N. 2° 12' W., bet. secs. 35 and 36.

Over mountainous land, covered with creosote, chaparral
and scattered cacti.

25.40

Ridge, bears E. and W.

40.10

Point for the true point for the ¼ sec. cor. of secs.
35 and 36, at proportionate distance; there is no
remaining evidence of the original corner. This point
falls on ledge where the corner can not be perpetuated.

From this point, point selected for the witness corner
of the ¼ sec. cor. of secs. 35 and 36, on the E-W
center line of sec. 36, bears N. 89° 46' E., 0.50 chs.
dist.

Set a stainless steel post, 28 ins. long, 2½ ins.
diam., on solid rock over a cross (X), in a mound of
stone, 4 ft. base to top, with brass cap mkd.