

493

DEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES  
T. 21 S., R. 59 E., MDM, NEVADA

CHAINS	Over rolling land, covered with creosote, chaparral and scattered cacti.
2.80	Trail road, bears NNE. and SSW.
39.90	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.  Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.  T21S R59E $\frac{1}{4} \begin{array}{r} S \ 2 \\ \hline S \ 11 \end{array}$  1987  Set a wooden post, 2 ins. square, 48 ins. long, alongside the stainless steel post.
52.00	Trail road, bears NNW. and SSE.
60.00	Enter Red Rock Wash, drains SE.
69.20	Leave Red Rock Wash, drains SE.
79.80	The cor. of secs. 2, 3, 10 and 11.
	<hr/> N. $2^{\circ} 33'$ W., bet. secs. 2 and 3.  Over rolling land, covered with creosote, chaparral and scattered cacti.
34.00	Enter Red Rock Wash, drains SE.
40.12	The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with a rebar, $\frac{5}{8}$ in. diam., firmly set 2 ins. below the ground, with aluminum cap mkd. ESI RLS 6902. This rebar correlates well with other existing original corners and is accepted as a careful and faithful perpetuation of the position of the original corner.  At the corner point  Not remonumented. Corner point falls in Red Rock Wash.  From this corner, the center of concrete culvert box, 8 ft. square, underneath Red Rock Detension Dam for flood control, bears N. $65^{\circ} 07'$ W., 9.79 chs. dist.
	<hr/> N. $2^{\circ} 33'$ W., beginning new measurement.  Over rolling land.
2.50	Leave Red Rock Wash, drains SE.
3.38	Point selected for the witness cor. of the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.  Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.