

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES
T. 21 S., R. 59 E., MDM, NEVADA

CHAINS	
82.72	The cor. of secs. 3, 4, 9 and 10.
	N. 2° 11' W., bet. secs. 3 and 4.
	Over rolling land, covered with creosote, chaparral and scattered cacti.
	35.90 Charleston Boulevard, bears NE. and SW.
	36.87 Point selected for the witness cor. of the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> WC T21S R59E $\frac{1}{4}$ S 4 S 3 1987 </div>
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	37.50 Enter Red Rock Wash, drains NE.
	40.72 True point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner, falls in Red Rock Wash, an unsafe place to perpetuate the corner.
	Set a 5/8 in. diam. rebar, 10 ins. long, flush with ground, in a mound of stone, 3 ft. base, 2 ft. high.
	55.50 Leave Red Rock Wash, drains NE.
	61.08 Point for the N 1/16 sec. cor. of secs. 3 and 4.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> N 1/16 S 4 S 3 1987 </div>
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	78.00 Ravine, drains SE.
	79.80 Power line, bears E. and W.
	79.95 Trail road, bears E. and W.
	80.30 The closing cor. of secs. 3 and 4, monumented with a limestone, 18X12X8 ins., firmly set in mound of stone, plainly mkd. with 3 grooves on E. and W. faces and 6 grooves on S. face, with RLS rebar, 5/8 in. diam., firmly set alongside, with aluminum cap mkd.