

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES
T. 21 S., R. 59 E., MDM, NEVADA

CHAINS	N. 89° 39' W., beginning new measurement. Over rolling land.
40.34	The cor. of secs. 4, 5, 8 and 9.
	N. 3° 03' W., bet. secs. 4 and 5. Over rolling land, covered with creosote, chaparral, and scattered cacti.
3.10	Charleston Boulevard, bears ENE. and WSW.
11.20	Enter Red Rock Wash, drains NE.
19.20	Leave Red Rock Wash, drains E.
40.06	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd. T21S R59E $\frac{1}{4}$ S 5 S 4 1987
40.20	Enter ravine, drains SE.
44.00	Leave ravine, drains SE.
78.20	Power line, bears E. and W.
79.00	Trail road, bears E. and W.
79.35	The closing cor. of secs. 4 and 5, monumented with a limestone, 16X12X8 ins., firmly set in a mound of stone, plainly mkd. with 2 grooves on W. face and 4 grooves on E. face and 6 grooves on S. face, with a rebar, $\frac{5}{8}$ in. diam., firmly set alongside, with aluminum cap mkd. NP CO LS 1798 32 <u>514</u> CIC This point now becomes an amended monument. Add the marks AM to the original cornerstone and deposit the stone alongside the rebar.
79.46	Intersect the Fifth Standard Parallel South. Point for the closing cor. of secs. 4 and 5. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.