


DEPENDENT RESURVEY OF CERTAIN LINES OF
MINERAL SURVEY NO. 4833,
T. 21 S., R. 59 E., MDM, NEVADA

CHAINS

A limestone ledge, 26X25 ins., 11 ins. above ground, bears N. 45° 24' E., 63 lks. dist., mkd. BO X D1-3-4833.

A limestone ledge, 42X25 ins., 16 ins. above ground, bears S. 70° 30' E., 33 lks. dist., mkd. BO X D1-3-4833.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.



1987

Thence S. 42° 10' W.

22.845 Cor. No. 4 of M.S. No. 4833, Dowling No. 1 lode, monumented with an iron post, 1½ ins. diam., firmly set in a mound of stone, with cap mkd. D1-4-4833.

Thence N. 59° 37' W.

5.051 Intersect the sec. line bet. secs. 15 and 16, at a point from which the ¼ sec. cor. of secs. 15 and 16, hereinbefore described, bears N. 0° 50' E., 2.418 chs. dist.

9.113 Cor. No. 1 of M.S. No. 4833, Dowling No. 1 lode and point of beginning.

SURVEY OF THE SUBDIVISION OF SECTION 3,
T. 21 S., R. 59 E., MOUNT DIABLO MERIDIAN, NEVADA

From the ¼ sec. cor. of secs. 3 and 10.

N. 2° 20' W., on the N-S center line of sec. 3.

Over rolling land, covered with creosote, chaparral and scattered cacti.

8.00 Ravine, drains NW.

33.20 Spur, project NW.

40.324 Intersect a rebar, 5/8 in. diam., firmly set in a mound of stone, with aluminum cap mkd. ESI RLS 6902. This position was not accepted because the N and W ¼ sec. cors. of sec. 3 and the closing cor. of secs. 3 and 4, were determined using improper resurvey procedures, based on Engineers & Surveyors Inc., map filed 8-7-86 in Clark County, Nevada Records, in book 860807, file 44, page 81.

40.42 Point for the center ¼ sec. cor. of sec. 3, at intersection with the E-W center line.