

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 N., R. 28 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
H. E. Franks and J. S. Mullen,
U.S. Deputy Surveyors, in 1904
and the Resurvey Executed by
E. Voigt, Cadastral Engineer, in 1922.

The cor. of Tps. 12 and 13 N., Rs. 28 and 29 E.,
monumented with an iron post, 3 ins. diam., firmly set
showing 8 ins. above ground, with brass cap mkd. as
described in the field notes of the dependent resurvey
of T. 12 N., R. 29 E., executed concurrently under this
same Group.

N. $89^{\circ} 57.9'$ W., bet. secs. 1 and 36.

Over gently rolling land, covered with scattered
sagebrush and rabbitbrush with cottonwood trees along
the Walker River.

10.003 Point for the E-E $1/64$ sec. cor. of secs. 1 and 36.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

S 36
E-E $1/64$ ———
S 1

1986

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of
cor.

From this corner, a fence corner, bears S. $82\frac{1}{4}^{\circ}$ W.,
0.51 chs. dist., from which fences bear S., E. and W.

19.333 Point selected for the witness E $1/16$ sec. cor. of
secs. 1 and 36.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24
ins. in the ground, with aluminum cap mkd.

WC
S 36
E $1/16$ ← ———
S 1

1986

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of
cor.

19.50 Left bank of Walker River, course SSE.