

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 13 N., R. 28 E., MDM, NEVADA

CHAINS

T13N R28E

$$\frac{1}{4} \begin{array}{r} S 16 \\ \hline S 21 \end{array}$$

1986

Deposit the original cornerstone alongside the aluminum post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.

DEPENDENT RESURVEY OF THE N $\frac{1}{2}$ SW $\frac{1}{4}$ NE $\frac{1}{4}$ OF SECTION 26,
IDENTICAL WITH INDIAN ALLOTMENT NO. 493,
T. 13 N., R. 28 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
E. Voigt, Cadastral Engineer
in 1922

The C-S-N 1/64 sec. cor. of sec. 26, monumented with an iron post, 1 in. diam., set flush with the surface of the ground, with brass cap mkd. as described in the field notes of the survey of the subdivision of sec. 26, T. 13 N., R. 28 E., executed under Group No. 66.

Remark the brass cap to read:

$$\begin{array}{c} C \\ S-N 1/64 | S 26 \\ C \end{array}$$

1922
1986

N. 0° 39.3' E., on the N-S center line of sec. 26.

Over gently rolling land.

6.30 Right bank Walker River, course SSE.

9.10 Left bank Walker River, course SSE.

10.053 The C-N 1/16 sec. cor. of sec. 26, monumented with an iron pipe, 1½ ins. diam., firmly set showing 6 ins. and in the corner of fences, from which fences bear N., S., E. and W. This iron pipe is locally recognized and is accepted as a careful and faithful perpetuation of the position of the original corner monumented in 1922.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with aluminum cap mkd.

$$\begin{array}{c} C \\ N 1/16 | S 26 \\ C \end{array}$$

1986