

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,  
T. 12 N., R. 29 E., MDM, NEVADA

CHAINS

WC  
S-N 1/64  
S 1 | S 6  
↓  
1986

Set a wooden post, 3 ins. square, 4 ft. long, alongside the aluminum post.

19.990 Point for the N 1/16 sec. cor. of secs. 1 and 6.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

N 1/16  
S 1 | S 6

1986

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor. This corner is located 0.04 chs. W. of the end of a fence, bearing N.

Enter cultivated fields of alfalfa.

29.985 Point for the N-N 1/64 sec. cor. of secs. 1 and 6.

Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

N-N 1/64  
S 1 | S 6

1986

This corner is located in a fence bearing N. and S.

39.980 The cor. of Tps. 12 and 13 N., Rs. 28 and 29 E., monumented with an iron post, 3 ins. diam., firmly set showing 8 ins. above ground, in an irrigation ditch, curving from E. to S., with brass cap mkd. as described in the field notes of the dependent resurvey of of T. 13 N., R. 29 E., executed under Group No. 181.

Add the marks "1986" to the brass cap.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,  
T. 12 N., R. 29 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
H. E. Franks and J. S. Mullen, U.S. Deputy Surveyors,  
in 1904,  
the Retracement Executed by  
E. Voigt, Cadastral Engineer, in 1920  
and the Resurvey Executed by C. S. Swanholm,  
Cadastral Engineer, in 1936.