DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 19 N., R. 44 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 19 N., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by U.S. Deputy Surveyors H. Thurtell and W. Kearney, in 1909.

The cor. of secs. 32 and 33, on the S. bdy. of the Tp., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 19 N., R. 44 E., executed under Group No. 573.

N. 88° 52' W., along the S. bdy. of sec. 32.

Over rolling mountainous land, covered with scattered sagebrush.

The cor. of secs. 4 and 5, T. 18 N., R. 44 E., monumented with a lava stone, 18X8X8 ins., firmly set 10 ins. in the ground and plainly mkd. with 4 notches on E. edge and 2 notches on W. edge, with a mound of stone S.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.

1982

Deposit the original cornerstone and set a steel fence post alongside the aluminum post.

N. 89° 59' W., beginning new measurement.

Over rolling mountainous land.

35.40 | Trail road, bears WNW. and ESE.

The ¼ sec. cor. of sec. 32, monumented with a granite stone, 16X10X10 ins., firmly set 12 ins. in the ground and plainly mkd. ¼ on N. face, with a mound of stone N.

At the corner point

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.