

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 19 N., R. 44 E., MDM, NEVADA

CHAINS		
	<p style="text-align: center;">T19N R44E S 31   S 32 <u>        </u> S 5 T18N</p> <p style="text-align: center;">1982</p> <p>Deposit the original cornerstone alongside the aluminum post.</p>	
<p>1.12</p>	<p>WEST, along the S. bdy. of sec. 31.</p> <p>Over rolling mountainous land, covered with scattered sagebrush.</p> <p>Point for the cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T19N S 31 <u>S 6   S 5</u> T18N R44E</p> <p style="text-align: center;">1982</p>	
<p>39.92</p>	<p>The ¼ sec. cor. of sec. 31, monumented with a granite stone, 15X14X10 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N. face, with a mound of stone N.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.</p> <p style="text-align: center;">T19N R44E <u>¼ S 31</u> T18N</p> <p style="text-align: center;">1982</p> <p>Deposit the original cornerstone alongside the aluminum post.</p>	
<p>1.14</p>	<p style="text-align: center;">_____</p> <p>N. 89° 51' W., beginning new measurement.</p> <p>Over rolling mountainous land.</p> <p>The ¼ sec. cor. of sec. 6, monumented with a granite stone, 16X10X8 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N. face.</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.</p>	