## DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY, T. 19 N., R. 44 E., MDM, NEVADA

		T. 19 N., R. 44 E., MDM, NEVADA
	CHAINS	WEST, bet. secs. 4 and 33.
		Over mountainous land, covered with sagebrush.
	1.00	Draw, drains NE.
	22.60	Draw, drains SE.
	40.12	The ¼ sec. cor. of secs. 4 and 33, monumented with a granite stone, 12X10X4 ins., firmly set 10 ins. in the ground and plainly mkd. ¼ on N. face.
		At the corner point
		Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with aluminum cap mkd.
		T20N R44E  S 33  S 4  T19N
		1982
		Deposit the original cornerstone alongside the aluminum post.
		S. 89° 57' W., beginning new measurement.
		Over mountainous land.
	40.03	The cor. of secs. 4, 5, 32 and 33, monumented with a granite stone, 16X10X6 ins., firmly set 10 ins. in the ground and plainly mkd. with 4 grooves on E. face, 2 grooves on the W. face, 19N on the N. face and 44E on the E. face, with a mound of stone W.
		At the corner point
		Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd.
		T20N R44E S 32 S 33 S 5 S 4 T19N
		1982
-	·	Deposit the original cornerstone alongside the aluminum post.
		From this corner, U.S.M.M. No. 5, monumented with a wooden post, 3X3X30 ins. long, plainly scribed USMM NO 5, firmly set in a mound of stone, 3 ft. base, 2 ft. high, bears S. 30° 43' W., 21.40 chs. dist.
		At the corner point
		Set an aluminum post, 30 ins. long, 2½ ins. diam.,

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd.