

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISIONAL LINES,
T. 19 N., R. 44 E., MDM, NEVADA

CHAINS

T19N R44E

S 6³/₄ S 5

1982

Deposit the original cornerstone alongside the aluminum post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

From this corner, Cor. No. 3 of M.S. No. 45, Mettacom lode, hereinbefore described, bears N. 86° 46' W., 23.03 chs. dist.

N. 0° 30' E., beginning new measurement.

Over rolling mountainous land.

8.60 New York Canyon Creek, 16 lks. wide, 12 ins. deep, course WSW.

10.40 Trail road, bears NW. and SE.

17.30 Trail road, bears NW. and SE.

42.89 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.

DEPENDENT RESURVEY OF M.S. NOS. 48, 92, 93, 101, 110, 112, 114, 122, 129, 137, 138 and 139 AND A PORTION OF M.S. NOS. 88, 104, 135, 136 AND 148, LOCATED IN SECS. 4 AND 5.

Reestablishment of the Survey Executed by U.S. Deputy Mineral Surveyor, W. L. DeWitt, in 1868.

Confidence lode

From Cor. No. 1 of M.S. No. 48, Confidence lode, monumented with a mound of stone. This mound of stone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an aluminum post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with aluminum cap mkd.

COR 1 | T19N
CON | R44E
MS 48 | S 5

1986