

250

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 45 N., R. 19 E., MDM, NEVADA

CHAINS		
	<p>Reestablishment of the Survey Executed by C. F. Putnam and W. F. Benson, U.S. Deputy Surveyors, in 1880.</p> <hr/> <p>From the cor. of Tps. 44 and 45 N., Rs. 19 and 20 E., monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 44 N., R. 19 E., executed under Group No. 622.</p> <p>N. 1° 42' W., bet. secs. 31 and 36.</p> <p>Over rolling land, through scattered sagebrush and bunchgrass.</p>	
39.69	<p>The ¼ sec. cor. of secs. 31 and 36, monumented with a trapstone, 13X11X8 ins., firmly set in a mound of stone and plainly mkd. ¼ on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T45N R19E R20E ¼ S 36 S 31</p> <p style="text-align: center;">1987</p> <p>Deposit the original cornerstone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	
	<hr/> <p>N. 0° 26' E., beginning new measurement.</p> <p>Over rolling land.</p>	
6.40	<p>Fence, bears E. and W., enter gently rolling reseeded land.</p>	
20.20	<p>Fence, bears E. and W.</p>	
40.23	<p>The cor. of secs. 25, 30, 31 and 36, monumented with a trapstone, 18X8X6 ins., firmly set in a mound of stone and plainly mkd. with 1 groove on S. face and 5 grooves on N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T45N R19E R20E S 25 S 30 S 36 S 31</p> <p style="text-align: center;">1987</p>	