

294

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 45 N., R. 19 E., MDM, NEVADA

<p>CHAINS 39.87</p>	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an unmarked trapstone, 16X8X4 ins., firmly set in a mound of stone. This unmarked trapstone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T45N R19E R20E S 1 S 6 S 12 S 7</p> <p style="text-align: center;">1987</p> <p>Deposit the unmarked trapstone and set a steel fence post, 5½ ft. long, alongside the iron post.</p>	
<p>40.50</p> <p>41.11</p>	<p>N. 0° 44' W., bet. secs. 1 and 6.</p> <p>Over rolling land, through scattered sagebrush and native grass.</p> <p>Fence, bears NE. and SW.</p> <p>The ¼ sec. cor. of secs. 1 and 6, monumented with a trapstone, 10X6X4 ins., firmly set in a mound of stone and dimly mkd. ¼ on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T45N R19E R20E ¼ S 1 S 6</p> <p style="text-align: center;">1987</p> <p>Deposit the original cornerstone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	
<p>8.30</p> <p>17.30</p>	<p>N. 0° 49' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>Creek, 10 lks. wide, 6 ins. deep, course SW.</p> <p>Trail road, bears E. and W.</p>	