

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 19 E., MDM, NEVADA

	CHAINS	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p> <p>N. 89° 35' W., bet. secs. 1 and 12.</p> <p>Over rolling land, through scattered sagebrush, greasewood and native grass.</p> <p>37.90 Trail road, bears N. and S.</p> <p>40.56 Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div>T45N R19E S 1 ¼ S T2</div> <p>1987</p> <p>Set a wooden post, 6 ft. long, 4 ins. square, alongside the iron post.</p> <p>43.00 Wash, 10 lks. wide, 1 ft. deep, drains S.</p> <p>59.90 Fence, bears NE. and SW.</p> <p>81.12 The cor. of secs. 1, 2, 11 and 12.</p>	
		<p>N. 1° 01' E., bet. secs. 1 and 2.</p> <p>Over rolling land, through scattered sagebrush, native grass and juniper.</p> <p>9.80 Bluff, bears NW. and SE.</p> <p>39.99 The ¼ sec. cor. of secs. 1 and 2, monumented with an unmarked trapstone, 15X7X6 ins., firmly set in a mound of stone, in a fence bearing N. and S. This unmarked trapstone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div>T45N R19E ¼ S 2 S 1</div> <p>1987</p> <p>Deposit the unmarked trapstone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	