

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 19 E., MDM. NEVADA

CHAINS		
69.10	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T45N S 2 MC ← S 11 R19E</p> </div> <p>1987</p> <p>Set a steel fence post, 5½ ft. long, alongside the iron post.</p> <p>Over water in Mosquito Lake.</p> <p>True point for the meander cor. of secs. 2 and 11, at record bearing and distance, from the cor. of secs. 1, 2, 11 and 12, falls in the lake and cannot be monumented.</p>	
6.85	<p>True point for the meander cor. of secs. 2 and 3, at record bearing and distance, from the ¼ sec. cor. of secs. 2 and 3, falls in the lake and cannot be monumented.</p> <p>NORTH, bet. secs. 2 and 3.</p> <p>Over water in Mosquito Lake.</p> <p>Point selected for the witness meander cor. of secs. 2 and 3, on the north bank of Mosquito Lake.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>WC T45N R19E S 3 S 2 MC</p> </div> <p>1987</p> <p>Set a wooden post, 5 ft. long, 4 ins. square alongside the iron post.</p> <p>Over nearly level land, through scattered sagebrush, greasewood and native grass.</p>	
7.20	<p>Improved gravel road, bears E. and W.</p>	
24.50	<p>Point for the ¼ sec. cor. of secs. 2 and 3, determined latitudinally at record distance from the closing cor. of secs. 2 and 3, and longitudinally at record distance from the ¼ sec. cor. of secs. 3 and 4, in a fence bearing WNW. and ESE. There is no remaining evidence of the original corner. The ¼ sec. cor. of secs. 3 and 4 bears N. 89° 49' W., 80.00 chs. dist.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T45N R19E ¼ S 3 S 2</p> </div> <p>1987</p>	