

325

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 45 N., R. 19 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T45N R19E S 9 S 10 1987</p> <p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post.</p> <hr/> <p>N. 0° 13' E., beginning new measurement.</p> <p>Over nearly level land.</p>
5.90	Fence, bears NNW. and SSE.
40.37	<p>The cor. of secs. 3, 4, 9 and 10, monumented with the decayed remains of a wooden post, loosely set in a mound of stone, with illegible scribe marks visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T45N R19E S 4 S 3 <hr/>S 9 S 10 1987</p> <p>Reset the original wooden post and set a steel fence post, 5½ ft. long, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/>
	<p>N. 0° 16' E., bet. secs. 3 and 4.</p> <p>Over nearly level land, through scattered sagebrush, greasewood and native grass.</p>
39.78	<p>Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T45N R19E S 4 S 3 1987</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>From this corner, a spring bears, N. 20° 18' E., 5.20 chs. dist.</p>
41.90	Enter rolling land.
49.00	Spur, projects E.