DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 45 N., R. 19 E., MDM, NEVADA

 	1. 45 N., R. 19 E., MDM, NEVADA
CHAINS	N. 0° 23' W., bet. secs. 4 and 5.
	Over mountainous land, through scattered sagebrush, native grass, juniper, mountain mahogany and aspen.
34.70	Enter flat, bears NW. and SE.
39.50	Point for the ½ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T45N_R19E
	S 5 S 4
	1987
	Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.
67.60	Spur, projects E.
76.92	Intersect the Ninth Standard Parallel North.
	Point for the closing cor. of secs. 4 and 5.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T46N R19E S 33 S 5 S 4
	C C T45N R19E
	1987
	Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this corner, the original closing cor. of secs. 4 and 5, monumented with a trapstone, 14X10X6 ins., firmly set in the center of a deeply embedded circle of stone, dimly mkd. CC on S. face, bears N. 0° 23' W., 0.32 chs. dist. Add the marks AM and bury the stone 6 ins. below the surface of the ground.
	From this same corner, the standard cor. of secs. 32 and 33, T. 46 N., R. 19 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 46 N., R. 19 E., executed concurrently under this same Group, bears S. 89° 54' W., 4.00 chs. dist.
	Point for the N ¼ sec. cor. of sec. 4 is on the Ninth Standard Parallel North and at midpoint between the closing cors.