

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 45 N., R. 19 E., MDM, NEVADA

CHAINS	
	Over mountainous land, through scattered sagebrush, native grass and juniper.
11.00	Trail road, bears N. and S.
13.70	Wash, 20 lks. wide, 2 ft. deep, drains N.
21.10	Low ridge, bears N. and S.
40.14	The ¼ sec. cor. of secs. 6 and 7, monumented with a trapstone, 14X11X10 ins., firmly set in a mound of stone and plainly mkd. ¼ on N. face.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T45N R19E
	$\frac{1}{4} \begin{array}{c} S \ 6 \\ \hline S \ 7 \end{array}$
	1987
	Deposit the original cornerstone alongside the iron post.
	<hr/>
	S. 88° 58' W., beginning new measurement.
	Over mountainous land.
44.20	Wash, 20 lks. wide, 1 ft. deep, drains N.
45.15	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.
	<hr/>
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0° 26' E., bet. secs. 5 and 6.
	Over mountainous land, through scattered sagebrush, native grass and juniper.
27.90	High voltage transmission line, bears N. 29½° W. and S. 29½° E.
31.20	Bladed road, parallels transmission line.
38.92	Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T45N R19E
	$S \ 6 \mid S \ 5$
	1987