

DEPENDENT RESURVEY OF THE NINTH STANDARD PARALLEL NORTH,
THROUGH RANGE 19 EAST, MDM, NEVADA

CHAINS	
	<p>The standard cor. of Tps. 46 N., Rs. 19 and 20 E., monumented with the decayed remains of a wooden post, loosely set in a deeply embedded mound of stone, with illegible scribe marks visible.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T46N R19E R20E <u>S 36 S 31</u></p>
	<p style="text-align: center;">1986</p>
	<p>Reset the decayed remains of the original wooden post and set a steel fence post, 5½ ft. long, alongside the iron post.</p>
	<p>N. 89° 37' W., along the S. bdy. of sec. 36.</p>
	<p>Over rolling land, through scattered sagebrush and bunchgrass.</p>
12.20	<p>Ravine, drains SE.</p>
22.10	<p>Ridge, bears N. and S.</p>
35.10	<p>Ravine, drains S.</p>
37.25	<p>The N ¼ sec. cor. of sec. 1, T. 45 N., R. 19 E., monumented with an iron post, 2½ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 45 N., R. 19 E., executed concurrently under this same Group.</p>
40.42	<p>The standard ¼ sec. cor. of sec. 36, monumented with a trapstone, 15X8X7 ins., firmly set in a mound of stone and dimly mkd. ¼ on N. face.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC T46N R19E <u>¼ S 36</u></p>
	<p style="text-align: center;">1986</p>
	<p>Deposit the original cornerstone and set a steel fence post, 5½ ft. long, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2ft. high, N. of cor.</p>
	<hr style="width: 20%; margin: auto;"/> <p>S. 89° 18' W., beginning new measurement.</p>
	<p>Over rolling land.</p>
11.40	<p>Fence, bears NW. and SE.</p>