

358

DEPENDENT RESURVEY OF THE NINTH STANDARD PARALLEL NORTH,
THROUGH RANGE 19 EAST, MDM, NEVADACHAINS
40.32

The standard $\frac{1}{4}$ sec. cor. of sec. 32, monumented with a trapstone, 29X4X4 ins., firmly set in a mound of stone and plainly mkd. $\frac{1}{4}$ on N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to solid rock and in a mound of stone, 5 ft. base to top, with brass cap mkd.

SC
T46N R19E
 $\frac{1}{4}$ S 32

1986

Deposit the original cornerstone alongside the iron iron post.

S. $89^{\circ} 53'$ W., beginning new measurement.

Over mountainous land.

7.70

Fence, bears NW. and SE.

12.20

Enter meadow, bears NW. and SE.

15.40

Creek, 10 lks. wide, 1 ft. deep, course NW.

26.70

Leave meadow, bears NW. and SE.

27.00

Trail road, bears NW. and SE.

35.84

The closing cor. of secs. 5 and 6, T. 45 N., R. 19 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 45 N., R. 19 E., executed concurrently under this same Group.

40.02

The standard cor. of secs. 31 and 32, monumented with a trapstone, 18X12X8 ins., firmly set in a mound of stone and plainly mkd. with 5 grooves on E. face and 1 groove on W. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

SC
T46N R19E
S 31 | S 32

1986

Deposit the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.

S. $89^{\circ} 46'$ W., along the S. bdy. of sec. 31.