DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 46 N. R. 19 E. MDM. NEVADA

	T. 46 N. R. 19 E. MDM. NEVADA
CHAINS	A juniper, 14 ins. diam., bears N. 69° W., 43 lks. dist., with illegible scribe marks visible on open blaze. (Record bearing, N. 60° W.)
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T46N R18E R19E
	\$ 12 S 7
	1986
	Reset the decayed remains of the original wooden post alongside the iron post.
	N. 0° 06' E., beginning new measurement.
	Over mountainous land.
40.24	The cor. of secs. 1, 6, 7 and 12, monumented with a trapstone, 22X20X8 ins., firmly set in a mound of stone and plainly mkd. with 5 grooves on S. face and 1 groove on N. face.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T46N R18E R19E S 1 S 6 S 12 S 7
	1986
	Deposit the original cornerstone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 0° 20' W., bet. secs. 1 and 6.
	Over mountainous land, through scattered sagebrush, bunchgrass and medium juniper.
21.50	Ravine, drains NW.
25.60	Trail road, bears E. and W.
37.40	Ravine, drains NE.
40.24	The ¼ sec. cor. of secs. 1 and 6, monumented with a trapstone, 36X14X4 ins., firmly set in a mound of stone and plainly mkd. ¼ on W. face, from which the original bearing tree:
1	· ·