

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 38 N., R. 68 E., MDM, NEVADA

CHAINS	
17.20	Trail road, parallels power line.
41.10	Trail road, bears E. and W.
41.27	<p>The cor. of secs. 11, 12, 13 and 14, monumented with a steel fence post, 18 ins. long, firmly set 2 ins. below the surface of the ground. This steel fence post agrees with distances as reported on plat number 75012 prepared by Alan S. Boyack, R.L.S. No. 2455, Nevada and on file at his office in Elko, Nevada and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T38N R68E S 11   S 12 S 14   S 13</p> <p style="text-align: center;">1986</p> <p>Reset the steel fence post and set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p>
<hr/>	
S. 89° 44' E., bet. secs. 12 and 13.	
Over nearly level land, covered with scattered sagebrush, greasewood, rabbitbrush, shadscale and native grass.	
7.70	Trail road, bears SSW. and NNE.
23.30	Improved gravel road, bears SW. and NE.
27.10	Power line, bears N. 43¼° E. and S. 43¼° W.
40.77	<p>The ¼ sec. cor. of secs. 12 and 13, monumented with a wooden post, 2X3 ins., 24 ins. long, with illegible scribe marks visible, wired to a steel fence post, firmly set and exposed 18 ins. above the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T38N R68E S 12 ¼ S 13</p> <p style="text-align: center;">1986</p> <p>Reset the original wooden post and the steel fence post, 3 ft. long, and set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p>
<hr/>	
N. 84° 51' E., beginning new measurement.	
Over nearly level land.	