DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 38 N., R. 68 E., MDM, NEVADA

T. 38 N., R. 68 E., MDM, NEVADA		
	CHAINS	N. 0° 53' E., beginning new measurement.
		Over nearly level land.
	41.45	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.
		Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		T38N R68E S 2 S 1 S 11 S 12
		1986
		Set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.
		S. 89° 54' E., bet. secs. 1 and 12.
		Over nearly level land, covered with scattered sagebrush, greasewood, shadscale, rabbitbrush and native grass.
	39.98	The ¼ sec. cor. of secs. 1 and 12, monumented with a wooden post, 2X3 ins., 26 ins. long, firmly set 12 ins. in the ground, with illegible scribe marks visible, with a steel fence post firmly set alongside and exposed 4 ft. above the ground.
		At the corner point
		Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		T38N R68E S 1 4 S T2
		1986
		Reset the original wooden post and the steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.
		N. 81° 48' E., beginning new measurement.
		Over nearly level land.
	31.60	Intersect the W. bdy. of sec. 6, T. 38 N., R. 69 E.
		Point for the closing cor. of secs. 1 and 12. This point is identical with a steel fence post, firmly set and exposed 12 ins. above the ground.