DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 38 N., R. 68 E., MDM, NEVADA

	1. 38 N., R. 68 E., MDM, NEVADA
CHAINS	N. 0° 27' E., bet. secs. 2 and 3.
	Over gently rolling land, covered with scattered sagebrush, rabbitbrush, shadscale, greasewood and native grass.
40.44	The ¼ sec. cor. of secs. 2 and 3, monumented with a wooden post, 1½x2 ins., 20 ins. long, with illegible scribe marks visible, wired to a steel fence post, firmly set and exposed 4 ft above the ground.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T38N R68E
	S 3 S 2
	1986
	Reset the original wooden post and the steel fence post, $5\frac{1}{2}$ ft. long, alongside the stainless steel post.
	N. 0° 08' E., beginning new measurement.
	Over gently rolling land.
40.19	The original closing cor. of secs. 2 and 3, monumented with a wooden post, 4 ins. square, 24 ins. long, loosely set in a mound of earth, with illegible scribe marks visible, with a steel fence post firmly set alongside and exposed 4 ft. above the ground. This point now becomes an amended monument. Scribe the marks "AM" on the wooden post and bury it alongside the steel fence post.
40.69	Intersect the S. bdy. of sec. 35, T. 39 N., R. 68 E.
	Point for the closing cor. of secs. 2 and 3.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T39N R68E
	1986
	Set a steel fence post, 5 ft. long, alongside the stainless steel post.
	From this corner, the cor. of secs. 34 and 35, T. 39 N.,