

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 39 N., R. 68 E., MDM, NEVADA

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T39N R68E

$$\begin{array}{r} \frac{1}{4} \\ \hline S\ 35\ | S\ 36 \end{array}$$

1986

Reset the original wooden post and steel fence post alongside the stainless steel post.

N. 0° 06' W., beginning new measurement.

Over gently rolling land.

40.69

The cor. of secs. 25, 26, 35 and 36, monumented with a wooden post, 2X4 ins., 30 ins. long, firmly set, with illegible scribe marks visible, with a steel fence post, 6 ft. long, alongside.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T39N R68E

$$\begin{array}{r} S\ 26\ | S\ 25 \\ \hline S\ 35\ | S\ 36 \end{array}$$

1986

Reset the original wooden post and steel fence post alongside the stainless steel post.

N. 89° 03' E., bet. secs. 25 and 36.

Over gently rolling land, through scattered sagebrush, greasewood and native grass.

38.45

The ¼ sec. cor. of secs. 25 and 36, monumented with a granite stone, 10X4X4 ins., loosely set and exposed 4 ins. above ground, plainly mkd. ¼ on N. face, with a steel fence post, 5 ft. long, alongside. (Record: wooden post.)

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T39N R68E

$$\begin{array}{r} S\ 25 \\ \frac{1}{4} \quad \hline S\ 36 \end{array}$$

1986

Deposit the original cornerstone and reset the steel fence post alongside the stainless steel post.
