

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 39 N., R. 68 E., MDM, NEVADA

CHAINS		
40.88	<p>The cor. of secs. 11, 12, 13 and 14, monumented with a wooden post, 4 ins. square, 18 ins. long, loosely set, with illegible scribe marks visible, with a steel fence post, 3 ft. long, firmly set and exposed 12 ins. above ground, alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39N R68E S 11 S 12 S 14 S 13</p> <p style="text-align: center;">1986</p> <p>Reset the original wooden post and steel fence post and set a steel fence post, 5 ft. long, alongside the stainless steel post.</p>	
34.40	<p>N. 89° 45' E., bet. secs. 12 and 13.</p> <p>Over gently rolling land, through scattered sagebrush, greasewood and native grass.</p>	
40.59	<p>Ridge, bears NNE. and SSW.</p> <p>The ¼ sec. cor. of secs. 12 and 13, monumented with a wooden post, 3 ins. square, 20 ins. long, firmly set, with illegible scribe marks visible, with a steel fence post, 3 ft. long, firmly set and exposed 12 ins. above ground, alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39N R68E S 12 ¼ S 13</p> <p style="text-align: center;">1986</p> <p>Reset the original wooden post and steel fence post alongside the stainless steel post.</p>	
9.00	<p>S. 87° 51' E., beginning new measurement.</p> <p>Over gently rolling land.</p>	
48.29	<p>Hoppie Creek, 20 lks. wide, 1 ft. deep, drains SE.</p> <p>Intersect the W. bdy. of sec. 7, T. 39 N., R. 69 E.</p> <p>Point for the closing cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	