

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL
NORTH, THROUGH A PORTION OF RANGE 68 EAST, MDM, NEVADA

CHAINS	
	<p>Reestablishment of the Survey Executed by J. C. Smyles and C. S. Preble, U. S. Deputy Surveyors, in 1881, and the Resurvey Executed by H. Fitzhugh, U. S. Deputy Surveyor, in 1894.</p> <hr/> <p>From the standard cor. of Tps. 41 N., Rs. 68 and 69 E., monumented with a stainless steel post, 2½ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 40 N., R. 69 E., executed concurrently under this same Group.</p> <p>S. 87° 53' W., along the S. bdy. of sec. 36.</p> <p>Over mountainous land, covered with medium pinon pine, juniper, scattered sagebrush, Brigham tea, bitterbrush, cacti and native grass.</p>
2.10	Spur, slopes S.
12.11	The N ¼ sec. cor. of sec. 6, T. 40 N., R. 69 E., monumented with a stainless steel post, 2½ ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 40 N., R. 69 E., executed concurrently under this same Group.
41.15	<p>Point for the standard ¼ sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC T41N R68E ¼ S 36</p> <hr style="width: 50%; margin: 0 auto;"/> <p>1986</p> </div> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p>
48.88	The closing cor. of Tps. 40 N., Rs. 68 and 69 E., monumented with a stainless steel post, 2½ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 40 N., R. 69 E., executed concurrently under this same Group.
54.90	Spur, slopes SE.
80.70	Trail road, bears NNW. and SSE.
82.30	<p>Point for the standard cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>