

126

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 38 N., R. 69 E., MDM, NEVADA

CHAINS	
	<div>T38N T38N R70E S 12 S 6 7CC R69E </div> <div>1986</div> <div>Deposit the original cornerstone alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 1½ ft. high, E. of cor.</div> <div>40.14</div> <div>The cor. of secs. 1 and 12, monumented with a granite stone, 20X12X8 ins., firmly set 10 ins. in the ground and plainly mkd. with 1 groove on N. face and 5 grooves on S. face, with steel fence posts, 3 ft. and 5 ft. long, firmly set alongside.</div> <div>At the corner point</div> <div>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</div> <div><div>T38N R69E T38N S 1 S 6 S 12 R70E</div><div>1986</div><div>Deposit the original cornerstone, reset the steel fence posts alongside the stainless steel post and raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.</div></div>
	<div>N. 0° 05' W., along the E. bdy. of sec. 1.</div> <div>Over rolling land, covered with medium sagebrush, scattered rabbitbrush, greasewood and native grass; along W. side of trail road bearing N. and S.</div> <div>39.31</div> <div>Point for the W ¼ sec. cor. of sec. 6, T. 38 N., R. 70 E., is at proportionate distance and on the E. bdy. of sec. 1.</div> <div>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</div> <div><div>T38N R69E R70E ¼ S 6</div><div>1986</div></div>