

DEPENDENT RESURVEY OF THE WEST BOUNDARY,  
T. 38 N., R. 69 E., MDM, NEVADA

CHAINS																						
18.60	Power line, bears N. 43¼° E. and S. 43¼° W.																					
20.00	Trail road, bears NE. and SW.																					
40.39	<p>The cor. of secs. 6, and 7, monumented with the decayed remains of a wooden post, loosely set in a mound of earth, with an unmarked quartzite stone, 11X9X4 ins., firmly set 5 ins. in the ground alongside, with a redwood post, 3X4 ins., 30 ins. long, lying alongside, with illegible scribe marks visible, with a steel fence post, 3 ft. long, firmly set alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td> </td><td>T38N</td><td></td></tr> <tr><td>T38N</td><td> </td><td>R69E</td><td></td></tr> <tr><td>S 12</td><td> </td><td>S 6</td><td></td></tr> <tr><td></td><td> </td><td>S 7</td><td></td></tr> <tr><td>R68E</td><td> </td><td></td><td></td></tr> </table> </div> <p>1986</p> <p>Reset the decayed remains of the original wooden post, the redwood post, and the steel fence post, deposit the unmarked stone and set a steel fence post, 5 ft. long, alongside the stainless steel post.</p>			T38N		T38N		R69E		S 12		S 6				S 7		R68E				
		T38N																				
T38N		R69E																				
S 12		S 6																				
		S 7																				
R68E																						
	<p>N. 0° 03' W., along the W. bdy. of sec. 6.</p> <p>Over gently rolling land, covered with scattered shadscale, sagebrush and native grass.</p>																					
18.19	<p>The closing cor. of secs. 1 and 12, T. 38 N., R. 68 E., monumented with a stainless steel post, 2½ ins. diam., firmly set showing 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 38 N., R. 68 E., executed concurrently under this same Group.</p>																					
40.25	<p>The W ¼ sec. cor. of sec. 6, monumented with a granite stone, 12X11X4 ins., firmly set 6 ins. in the ground and plainly mkd. ¼ on E. face. This point was reestablished by W. H. Settlemeyer and is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td></td><td>T38N</td><td></td></tr> <tr><td>R68E</td><td></td><td>R69E</td><td></td></tr> <tr><td></td><td> </td><td>¼</td><td></td></tr> <tr><td></td><td> </td><td>S 6</td><td></td></tr> </table> </div> <p>1986</p>			T38N		R68E		R69E				¼				S 6						
		T38N																				
R68E		R69E																				
		¼																				
		S 6																				