

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 39 N., R. 69 E., MDM, NEVADA

CHAINS	
	<p>Reestablishment of the Survey Executed by J. C. Smyles and C. S. Preble, U.S. Deputy Surveyors, in 1881.</p> <hr/> <p>From the cor. of Tps. 38 and 39 N., Rs. 69 and 70 E., monumented with a stainless steel post, 2½ ins. diam., firmly set and exposed 4 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 38 N., R. 69 E., executed concurrently under Group No. 636.</p> <p>N. 0° 34' E., bet. secs. 31 and 36.</p> <p>Over gently rolling land, through scattered sagebrush, greasewood and native grass.</p>
5.00	Trail road, bears WNW. and ESE.
39.88	<p>Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39N R69E R70E ¼ S 36 S 31 1986</p> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <p>From this corner, a steel fence post, exposed 15 ins. above ground, bears N. 83° 07' E., 0.95 chs. dist.</p>
53.60	Wash, 30 lks. wide, 6 ft. deep, drains W.
79.76	<p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39N R69E R70E S 25 S 30 S 36 S 31 1986</p> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p>
29.30	Trail road, bears NE. and SW.
39.40	Trail road, bears WNW. and ESE.
	<p>N. 0° 34' E., bet. secs. 25 and 30.</p> <p>Over gently rolling land, through scattered sagebrush, greasewood and native grass.</p>