

DEPENDENT RESURVEY OF THE EIGHTH STANDARD PARALLEL,
THROUGH RANGE 69 EAST, MDM, NEVADA

CHAINS	
40.00	<p>The standard cor. of secs. 31 and 32, monumented with a granite stone, 12x8x6 ins., firmly set 6 ins. in the ground and plainly mkd. with 1 groove on W. face, 5 grooves on E. face and SC on N. face, with a steel fence post, 5½ ft. long, firmly set alongside, with a mound of stone N. This marked stone correlates well with other existing original corners and is accepted as the best available evidence of the position of the original corner. (Record: wooden post)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R69E <u>S 31 S 32</u></p> <p style="text-align: center;">1986</p> <p>Deposit the marked cornerstone; reset the steel fence post, alongside the stainless steel post and rebuild the mound of stone, 3 ft. base, 1½ ft. high, N. of cor.</p>
41.15	<p>S. 87° 53' W., along the S. bdy. of sec. 31.</p> <p>Over rolling land, covered with medium sagebrush, scattered cacti, juniper, rabbitbrush and native grass.</p> <p>Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T41N R69E <u>¼ S 31</u></p> <p style="text-align: center;">1986</p> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p>
53.30	Fence, bears NNW. and SSE.
55.49	The closing cor. of secs. 5 and 6, T. 40 N., R. 69 E., hereinafter described.
82.30	Point for the standard cor. of Tps. 41 N., Rs. 68 and 69 E., at proportionate distance; there is no remaining evidence of the original corner.