

284

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 40 N., R. 69 E., MDM, NEVADA

CHAINS	
	<p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p> <p>S. 89° 22' W., bet. secs. 1 and 12.</p> <p>Over rolling land, covered with scattered sagebrush, rabbitbrush, greasewood, shadscale and native grass.</p>
27.80	Spur, slopes S.
40.31	<p>Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T40N R69E S 1 ¼ S 12 1986</p> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p>
80.62	The cor. of secs. 1, 2, 11 and 12.
40.88	<p>N. 1° 00' W., bet. secs. 1 and 2.</p> <p>Over rolling land, covered with medium sagebrush, scattered juniper, shadscale and native grass.</p> <p>Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T40N R69E S 2 1 ¼ S 1 1986</p> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post.</p>