

330

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 40 N., R. 70 E., MDM, NEVADA

CHAINS	
	<p>The cor. of secs. 4, 5, 32 and 33, monumented with a redwood post, 4 ins. square, 24 ins. long, firmly set in a mound of earth alongside a steel fence post.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T40N R70E S 32   S 33 S 5   S 4 T39N</p> </div> <p>1986</p> <p>Reset the original wooden post and set a steel fence post, 5½ ft. long, alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>N. 89° 22' W., bet. secs. 5 and 32.</p> <p>Over gently rolling land, through scattered sagebrush, greasewood and native grass.</p>
27.00	Improved gravel road, parallels power line.
27.70	Power line, bears N. 34¾° W. and S. 34¾° E.
40.26	<p>Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T40N R70E S 32 ¼ S 5 T39N</p> </div> <p>1986</p> <p>Set a steel fence post, 5½ ft. long, alongside the stainless steel post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
51.10	Wash, 100 lks. wide, 2 ft. deep, drains N.
80.52	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>