SURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 12 N., R. 68 E., MDM, NEVADA

	T. 12 N., R. 68 E., MDM, NEVADA
CHAINS	T12N R68E S 35 S 2 T11N
	1987
	This cor. is located on steep easterly slope in cliffs.
62.40	Ravine, drains S.
80.00	Point for the cor. of secs. 1, 2, 35 and 36, NORTH, 7.3 lks. from the tangent. This point falls on ledge where a permanent monument cannot be perpetuated.
	From this point, point selected for the witness corner of the cor. of secs. 1, 2, 35 and 36, bears N. 88° 37' E., 0.74 chs. dist.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock over a cross (X), and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	WC T12N R68E
	1987
	Land, mountainous. Soil, rocky. Undergrowth, sagebrush and native grass. Timber, limber pine, mountain mahogany and aspen.
	EAST, bet. secs. 1 and 36, on a transit line describing the tangent.
	Over mountainous land, covered with medium timber and sparse undergrowth.
3.20	Spur, projecting S.
12.70	Ravine, drains S.
40.00	Point for the ¼ sec. cor. of secs. 1 and 36, NORTH, 10.0 lks. from the tangent.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T12N R68E S 36 S 1 T11N
	1987
48.99	Point selected for a witness point, NORTH, 10.6 lks. from the tangent.
1	