

387

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 68 E., MDM, NEVADA

CHAINS

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 13 N., R. 68 E., MOUNT DIABLO MERIDIAN, NEVADA

The cor. of secs. 32 and 33, T. 14 N., R. 68 E., monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of T. 14 N., R. 68 E., executed under Group No. 266, from which the original bearing trees:

A mahogany, 8 ins. diam., bears N. 35° E., 85 lks. dist., with partially healed blaze.

A fir, 24 ins. diam., bears N. 45 $\frac{3}{4}$ ° W., 339 lks. dist., with healed blaze.

Remark the brass cap to read as follows:

T14N R68E
S 32 | S 33
S 5 | S 4
T13N

1987
1940

S. 0° 03' E., bet. secs. 4 and 5.

Over mountainous land, covered with medium timber and undergrowth.

15.00 Spur, projects W.

28.00 Ravine, drains W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 6 ft. base to top, with brass cap mkd.

T13N R68E
 $\frac{1}{4}$
S 5 | S 4

1987

This corner is located on a spur projecting W.

54.20 Board Creek, 10 lks. wide, 1 ft. deep, course W.

74.20 Spur, projects WNW., just above ledges.

80.00 Point for the cor. of secs. 4, 5, 8 and 9.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T13N R68E
S 5 | S 4
S 8 | S 9

1987